


G13	G5				
230 V		6 W	18 W		
		8 W	30 W		
		13 W	36 W		
		15 W	58 W		
				T5	T8
					


- Faible hauteur
- Encombrement réduit
- Alimentation électronique intégrée



960 °C F IP 20 CE

Code	Désignation	U service	P	Culot	Dimensions					Masse	U.R.
		V	W		A	B	C	D	E	g	
06106-E	MRL 1 LAMPE 6W	230	6	G 5	231	Clips		30	53		15
06108-E	MRL 1 LAMPE 8W	230	8	G 5	307	169		30	53		15
06113-E	MRL 1 LAMPE 13W	230	8	G 5	536	398		30	53		15
06115-E	MRL 1 LAMPE 15W	230	15	G 13	459	321		32	66		15
06118-E	MRL 1 LAMPE 18W	230	18	G 13	611	473		32	66		15
06130-E	MRL 1 LAMPE 30W	230	30	G 13	916	778		32	66		12
06136-E	MRL 1 LAMPE 36W	230	36	G 13	1221	1083		32	66		12
06158-E	MRL 1 LAMPE 58W	230	58	G 13	1521	1383		32	66		6

EXEMPLES DE PRE CABLAGE



Héliophane sarl

Le Prieuré
2, rue de la mairie
F88600 AYDOILLES

4, monté de Vourlat
F42000 SAINT ÉTIENNE



courrier@heliophane.com

APPAREILLAGE