




E27 E40	160 W 250 W 500 W	➤ Alimentation directe sur le secteur ➤ Durée de vie très élevée ➤ <u>Positions de fonctionnement</u>
230 V		
		 160 W  250 W  500 W



Code	Désignation	U service	I	P	Culot	Dimensions		T°	Flux	Efficacité	Durée de vie	IRC	U.R.
		V	A	P		L	Ø	K	lm	lm/w	h		
20414	HSB-BW 160	230	0,80	160	E27	178	76	3500	3100		16000	42	40
20415	HSB-BW 250	230	1,20	250	E40	227	91	3500	5600		16000	42	12
20456	HSB-BW 500	230	2,40	500	E40	292	122	3500	14000		16000	42	12

SPECTRES D'ÉMISSION




Heliophane

Le Prieuré
2, rue de la mairie
F88600 AYDOILLES

4, montée de Vourlat
F42000 SAINT ETIENNE


courier@heliophane.com

SOURCES

E27	50 W	400 W	➤ Rendu des couleurs = 42 ➤ Durée de vie très élevée ➤ <u>Position de fonctionnement :</u> 
E40	80 W	700 W	
Self	125 W	1000 W	
	250 W		
			



Code	Désignation	U	I	P	Culot	Dimensions		T°	Flux	Efficacité	Durée de vie	IRC	U.R.
		service				L	Ø	K	lm	lm/w	h		
20405	HSL-BW 50	95	0,61	50	E27	130	56	4000	1800		29000	42	40
20406	HSL-BW 80	115	0,80	80	E27	166	71	4000	3800		29000	42	40
20407	HSL-BW 125	125	1,15	125	E27	178	76	4000	6300		29000	42	40
20408	HSL-BW 250	130	2,13	250	E40	227	91	4000	13000		29000	42	12
20409	HSL-BW 400	135	3,25	400	E40	292	122	4000	22000		29000	42	12
20410	HSL-BW 700	140	5,40	700	E40	357	152	4000	4000		21500	42	6
20411	HSL-BW 1000	145	7,50	1000	E40	411	167	4000	5800		21500	42	6

EQUIPEMENTS ANNEXES



- Alimentation CL I
- Alimentation IP 54



Héliophane sarl

Le Prieuré
2, rue de la mairie
F88600 AYDOILLES

4, montée de Vourlat
F42000 SAINT ETIENNE


courrier@heliophane.com

SOURCES